


ANGLE GRINDERS & SANDERS

ARO ELITE ERGONOMIC HANDLE DESIGN

GR03A-20C-2



Model	Free Speed RPM	Rated Power HP kW	Collet/ Spindle Thd. in. mm	Spindle Offset in. mm	Overall Length in. mm	Weight lb. kg	Sound Level* dB(A)	Abrasive Type & Cap.
E3 SERIES with Collet								
GR03A-20C-2	20,000	0.30 0.22	1/4" - 6	0.75 19	6.1 154	1.1 0.51	74	1" Carb. Burr, 1" Mtd. Stone, 2" or 3" Sanding Pad
GR03A-12C-2	12,000	0.24 0.18	1/4" - 6	0.75 19	6.1 154	1.1 0.51	74	

DOTCO® CARBIDE BUR & MOUNTED WHEEL GRINDERS/SANDERS

Ergonomic Series 12-12 (right angle)

Nominal .3 HP – Front & Rear Exhaust

**Capacity: 1/2" Carbide Bur
1" Mounted Wheel**

Air Inlet: Front Exhaust: 1/4" N.P.T.F. – Use 1/4" (6.4 mm) I.D. Hose
Rear Exhaust: 1/8" N.P.T.F. – Use 1/4" (6.4 mm) I.D. Hose

Angle Head Height: 2.9" (74 mm) over spindle

Specifications @ 90 psi (620 kPa) maximum air pressure.

Model Number w/lever throttle*	Speed RPM	Standard Collet	Weight		Length	
			lbs.	kgs	in.	mm
Series 300 – Collet Chuck – Front Exhaust						
12L1200-36	12,000	1/4"	1.09	.49	6.25	158
12L1201-36	20,000	1/4"	1.09	.49	6.25	158
Series 300 – Collet Chuck – Rear Exhaust						
12L1280-36	12,000	1/4"	1.09	.49	6.25	158
12L1281-36	20,000	1/4"	1.09	.49	6.25	158

* For Lock-Off Lever Throttle, substitute "S" for "L" in model number.

STANDARD EQUIPMENT:

1/4" (308) collet, collet wrenches, and speed regulator.

OPTIONAL EQUIPMENT:

Extra Cost: Air supply hoses (front exhaust models), Filter-regulator-lubricator – 45-0240B, Belt Sander, Rivet Trimmer Attachment, PSA Disc Holders, Series 300 collet 3/64" (301) thru 3/32" (303), Overhose (rear exhaust models)

Capacity: 2" or 3" Sanding Discs

Angle Head Height: Threaded Spindle (-32), 1.85" (47 mm) over spindle

Model Number w/lever throttle*	Speed RPM	Capacity	Weight		Length	
			lbs.	kgs	in.	mm
1/4"-28 Internal Thread Spindle – Front Exhaust						
12L1200-32	12,000	3"	1.05	.48	6.25	159
12L1201-32	20,000	2"	1.05	.48	6.25	159

